

# PH SERIES



600 pW to 750 mW, Si and Ge Photo Detectors



Monitors

Energy Detectors

Power Detectors

OEM Detectors

Calorimeters

Diffraction Optics

Beam Diagnostics



PH100-Si



## Key Features

- 1 **Large Apertures**  
11.28 mm Ø for the Silicon versions
- 2 **3 Versions**
  - . Silicon  
300 - 1100 nm, up to 750 mW
  - . Silicon-UV  
200 - 900 nm, up to 30 mW
  - . Germanium  
800 - 1650 nm, up to 500 mW
- 3 **Choice of Attenuators**

OD-1	OD-2
10% Transmission	1% Transmission
- 4 **Precise Calibration**  
Wavelength selection in 1 nm steps
- 5 **Smart Interface**  
Containing all the calibration data

### See also

- . Calibration .....6
- . Compatible monitors
  - SOLO 2 ..... 20
  - UNO ..... 22
  - P-LINK ..... 26




## Accessories

### » Pelican Carrying Case

We offer a robust hard shell polymer carrying case.



## SPECIFICATIONS

Models	PH100-Si	PH-100Si <sup>UV</sup>	PH20-Ge
			
Max Measurable Power	30 mW	28 mW	30 mW
Max Measurable Power (with OD-2)	750 mW	50 mW	500 mW

MEASUREMENT CAPABILITY	PH100-Si	PH-100Si <sup>UV</sup>	PH20-Ge
Spectral Range	300 – 1100 nm	200 – 900 nm	800 – 1650 nm
With OD-1	400 – 1100 nm	400 – 900 nm	900 – 1650 nm
With OD-2	630 – 1100 nm	630 – 900 nm	950 – 1650 nm
Maximum Measurable Power	30 mW @ 1064 nm	2.8 mW @ 532 nm	30 mW @ 1064 nm
With OD-1	300 mW @ 1064 nm	25 mW @ 532 nm	300 mW @ 1064 nm
With OD-2	750 mW @ 1064 nm	30 mW @ 850 nm	500 mW @ 1064 nm
Minimum Measurable Power <sup>a</sup>	600 pW @ 980 nm	600 pW @ 850 nm	2 nW @ 1550 nm
With OD-1	6 nW @ 980 nm	6 nW @ 850 nm	20 nW @ 1550 nm
With OD-2	60 nW @ 980 nm	60 nW @ 850 nm	200 nW @ 1550 nm
Rise Time (nominal)	0.2 sec	0.2 sec	0.2 sec
Peak Sensitivity	0.5 A/W	0.45 A/W	0.98 A/W
Calibration Uncertainty	±6.5 % 300 - 399 nm ±2.5 % 400 - 999 nm ±5 % 1000 - 1049 nm ±7 % 1050 - 1100 nm	±8 % 200 - 219 nm ±6.5 % 220 - 399 nm ±2.5 % 400 - 900 nm	±3.5 % 800 - 1650 nm
Accuracy (with OD filters)	±5 %	±5 %	±5 %

## DAMAGE THRESHOLDS

Maximum Average Power Density	100 W/cm <sup>2</sup>	100 W/cm <sup>2</sup>	100 W/cm <sup>2</sup>
Saturation Level	30 mW/cm <sup>2</sup> @ 1064 nm	55 mW/cm <sup>2</sup> @ 532 nm	320 mW/cm <sup>2</sup> @ 1064 nm

## PHYSICAL CHARACTERISTICS

Effective Aperture Diameter	11.28 mm Ø	11.28 mm Ø	5 mm Ø
Dimensions	36 mm Ø x 26.5D mm	36 mm Ø x 26.5D mm	36 mm Ø x 26.5D mm
Weight (head only)	130 g	130 g	130 g

## ORDERING INFORMATION

Full Product Name	PH100-Si	PH100-Si <sup>UV</sup>	PH20-Ge
Product Number	200878	200879	200866
Full Product Name	PH100-Si-OD1	PH100-Si <sup>UV</sup> -OD1	PH20-Ge-OD2
Product Number	200880	200881	200874
Full Product Name	PH100-Si-OD2	PH100-Si <sup>UV</sup> -OD2	PH20-Ge-OD2
Product Number	200882	200883	200875

a. Half hour warm-up before offset nulling. Offset nulling on the lowest scale after each new power supply. Temperature ± 0.5 °.

## America

Canada  
United States  
South America

## Europe

Austria  
Belgium  
France  
Germany  
Ireland  
Italy  
Poland  
Russia  
Spain  
Sweden  
Scandinavia  
Switzerland  
The Netherlands  
Turkey  
United Kingdom

## Asia Pacific

China  
India  
Indonesia  
Israel  
Japan  
Korea  
Malaysia  
Philippines  
Singapore  
Taiwan  
Thailand  
Vietnam

## Oceania

Australia  
New Zealand



# gentec-EO

## Leader in Laser Beam Measurement Since 1972

### Headquarters

445 St-Jean-Baptiste, Suite 160  
Québec, QC, G2E 5N7, CANADA

T (418) 651-8003  
F (418) 651-1174  
1.888.5Gentec (543.6832)

[info@gentec-eo.com](mailto:info@gentec-eo.com)

### Calibration Centers

Quebec City, Canada  
Olching (Munich), Germany

### Distributed in the UK by

**Lambda**  
photometrics  $\lambda$

Batford Mill, Harpenden, Herts., UK, AL5 5BZ

T +44 (0) 1582 764334  
F +44 (0) 1582 712084

[info@lambdaphoto.co.uk](mailto:info@lambdaphoto.co.uk)  
[www.lambdaphoto.co.uk](http://www.lambdaphoto.co.uk)

[www.gentec-eo.com](http://www.gentec-eo.com)