

QE25



25 x 25 mm, 2 μ J - 20 J



Key Features

- 1 **Modular Concept**
Increase the power capability of your detector : 2 different cooling modules
- 2 **Low Noise Level**
2 μ J for the MT coating
- 3 **Test Target Included**
With the MB models
- 4 **Available with Metallic Absorber**
High Repetition Rate (6000 Hz)
- 5 **Noise Reduction Stand**
Delrin post to reduce noise coming from exterior vibrations
- 6 **Smart Interface**
Containing all the calibration data



Diamond Configuration

See also

. How it works	12
. Calibration	6
. Detailed dimensions	43
. Spectral absorption	106
. Compatible monitors	
SOLO 2	20
S-LINK-2	24

Accessories

» QEA/QED Attenuators

15 - 20% transmittance
400 nm - 2.5 μ m : QEA
190 nm - 2.5 μ m : QED



» DB-15 to BNC Adaptor

Make your QE Series detector compatible with your oscilloscope.



» Pelican Carrying Case

We offer a robust hard shell polymer carrying case.



SPECIFICATIONS

Models	QE25LP-S-MB	QE25LP-H-MB	QE25SP-S-MT	QE25SP-H-MT
Max Measurable Energy (with Attenuator)	20 J	20 J	10 J	10 J
Max Repetition Frequency	300 Hz	300 Hz	6000 Hz	6000 Hz





MEASUREMENT CAPABILITY	S-MB		H-MB		S-MT		H-MT	
Spectral Range	0.19 – 20 μm		0.19 – 20 μm		0.19 – 20 μm		0.19 – 20 μm	
Maximum Measurable Energy	Alone	Attenuator	Alone	Attenuator	Alone	Attenuator	Alone	Attenuator
1064 nm, 7 ns, 10 Hz ^a	3.8 J	20 J	3.8 J	20 J	3.0 J	10 J	3.0 J	10 J
266 nm, 7 ns, 10 Hz	3.1 J	4.8 J	3.1 J	4.8 J	0.44 J	1.5 J	0.44 J	1.5 J
Noise Equivalent Energy ^b	4 μJ		4 μJ		2 μJ		2 μJ	
Sensitivity ^{c, d}	10 V/J		10 V/J		20 V/J		20 V/J	
Max Repetition Frequency	300 Hz		300 Hz		6000 Hz		6000 Hz	
Maximum Pulse Width (typical)	400 μs *		400 μs *		10 μs		10 μs	
Rise Time (typical 0-100%)	550 μs		550 μs		20 μs		20 μs	
Calibration Uncertainty ^e	± 3 %		± 3 %		± 3 %		± 3 %	
Repeatability	<0.5 %		<0.5 %		<0.5 %		<0.5 %	

DAMAGE THRESHOLDS

	S-MB		H-MB		S-MT		H-MT	
Maximum Average Power All Wavelengths	Alone	Attenuator	Alone	Attenuator	Alone	Attenuator	Alone	Attenuator
	5 W	15 W	10 W	30 W	5 W	15 W	10 W	30 W
Maximum Energy Density	Alone	Attenuator	Alone	Attenuator	Alone	Attenuator	Alone	Attenuator
1064 nm, 7 ns, 10 Hz	0.6 J/cm ²	7 J/cm ²	0.6 J/cm ²	7 J/cm ²	0.50 J/cm ²	2 J/cm ²	0.50 J/cm ²	2 J/cm ²
532 nm, 7 ns, 10 Hz	0.6 J/cm ²	5 J/cm ²	0.6 J/cm ²	5 J/cm ²	0.07 J/cm ²	0.35 J/cm ²	0.07 J/cm ²	0.35 J/cm ²
266 nm, 7 ns, 10 Hz	0.5 J/cm ²	1 J/cm ²	0.5 J/cm ²	1 J/cm ²	0.07 J/cm ²	0.30 J/cm ²	0.07 J/cm ²	0.30 J/cm ²

Choice of Attenuator : QEA-25 (0.4 – 2.5 μm) or QED-25 (0.19 – 2.5 μm)

PHYSICAL CHARACTERISTICS

Effective Aperture (with Attenuator)	25 X 25 mm (22 X 22 mm)			
Absorber				
	Multi-Band	Multi-Band	Metallic	Metallic
Dimensions	50H x 50W x 14D mm	50H x 50W x 52.5D mm	50H x 50W x 14D mm	350H x 50W x 52.5D mm
Weight	120 g	187 g	120 g	187 g

ORDERING INFORMATION

Full Product Name	QE25LP-S-MB	QE25LP-H-MB	QE25SP-S-MT	QE25SP-H-MT
Product Number (including stand)	200312	200313	200310	200311

*Also available on special order: The Extra Long Pulse Series QE25-ELP-MB for pulse widths up to 4 msec, custom-tuned for rep. rate, sensitivity, and pulse width.

a. Increasing pulse width increases the maximum measurable energy.

b. Nominal value, actual value depends on electrical noise in the measurement system.

c. Load: 1 M Ω and \leq 130 pF.

d. Maximum output voltage = sensitivity x maximum energy.

e. Excludes non-linearities.

America

Canada
United States
South America

Europe

Austria
Belgium
France
Germany
Ireland
Italy
Poland
Russia
Spain
Sweden
Scandinavia
Switzerland
The Netherlands
Turkey
United Kingdom

Asia Pacific

China
India
Indonesia
Israel
Japan
Korea
Malaysia
Philippines
Singapore
Taiwan
Thailand
Vietnam

Oceania

Australia
New Zealand



gentec-EO

Leader in Laser Beam Measurement Since 1972

Headquarters

445 St-Jean-Baptiste, Suite 160
Québec, QC, G2E 5N7, CANADA

T (418) 651-8003
F (418) 651-1174
1.888.5Gentec (543.6832)

info@gentec-eo.com

Calibration Centers

Quebec City, Canada
Olching (Munich), Germany

Distributed in the UK by

Lambda
photometrics λ

Batford Mill, Harpenden, Herts., UK, AL5 5BZ

T +44 (0) 1582 764334
F +44 (0) 1582 712084

info@lambdaphoto.co.uk
www.lambdaphoto.co.uk

www.gentec-eo.com