

SOLO 2



Single Channel, Power & Energy Monitor



Monitors

Energy Detectors

Power Detectors

OEM Detectors

Calorimeters

Diffractive Optics


Beam Diagnostics



Key Features

- 1 **Reads ALL Detector Types**
Thermopile, photo and pyroelectric detectors
- 2 **Large LCD Display**
77 x 58 mm with super bright backlight
- 3 **Unique Ergonomic Design**
Great for both handheld and tabletop use
- 4 **Shift-Key and Single-Key Navigation**
Direct access and shift access to the main functions
- 5 **Internal Data Storage**
225 000 points internal data storage space
- 6 **Real-Time Statistical Functions**
Max, Min, Average, Standard Deviation, RMS and PTP Stability, Pulse # and Repetition Rate
- 7 **Available Outputs**
Analog Output, RS-232, USB

NEW



Accessories

- » **External Power Supply**
Additional 9 Volt power supply.
- » **USB Cable**
Additional USB Cable.
- » **RS-232 Cable**
Optionnal RS-232 Cable

- » **Protective Pouch**
Protect your monitor from scratches and dust.



- » **Pelican Carrying Case**
We offer a robust hard shell polymer carrying case.



SPECIFICATIONS

Model	SOLO 2
--------------	--------



Detector Types	Thermopiles, Photo Detectors, Pyroelectrics
-----------------------	---

Display	LCD with Backlight
----------------	--------------------

POWER METER SPECIFICATIONS	SOLO 2
-----------------------------------	--------

Power Range	
Thermopile	1 μ W to 30 kW
Photo Detector	4 pW to 3 W
Monitor Accuracy	± 0.5 % full scale
Statistics	Current Value, Max, Min, Average, Standard Deviation, RMS & PTP Stability, Time

ENERGY METER SPECIFICATIONS	
------------------------------------	--

Energy Range	0.1 μ J to 30 kJ
Monitor Accuracy	± 1 % full scale (<500 Hz)
Software Trigger Level	0.1 to 99.9%, 0.1% resolution, default 2% (3% for MT)
Repetition Rate	3 000 Hz / 10 000 Hz in sampling
Statistics	Current Value, Max, Min, Average, Std Dev., RMS & PTP Stability, Pulse #, Rep. Rate and Avg Power

DETECTOR COMPATIBILITY	
-------------------------------	--

Thermopile	Average Power & Single Shot Energy
Photo Detector	Average Power (mW, dBm)
Pyroelectric	Pulse Energy

GENERAL SPECIFICATIONS	
-------------------------------	--

Digital Display Size	77 x 58 mm LCD - 240 x 160 pixels
Digit Height	23 mm
Data Display	Real Time, Line Plot, Histogram, Statistics, Digital Tuning Needle
Analog Output	0-1 Volt, Full Scale, ± 1 %
Serial Commands and Data Transfer Via	USB (standard) or RS-232 (cable in option)
Real-Time Data Transfer Rate	200 Hz
Data Storage Capacity	225 000 Points
Dimensions	210W x 122H x 44D mm
Weight (With Batteries)	0.52 kg
Battery Type	4 x Rechargeable 1.2 V Ni-MH AA
Battery Life	11 hours, 6 hours with backlight
External Power Supply	100/240 VAC 50-60 Hz to 9 VDC 1.66 A

ORDERING INFORMATION	
-----------------------------	--

Full Product Name	SOLO 2
Product Number	200954

America

Canada
United States
South America

Europe

Austria
Belgium
France
Germany
Ireland
Italy
Poland
Russia
Spain
Sweden
Scandinavia
Switzerland
The Netherlands
Turkey
United Kingdom

Asia Pacific

China
India
Indonesia
Israel
Japan
Korea
Malaysia
Philippines
Singapore
Taiwan
Thailand
Vietnam

Oceania

Australia
New Zealand



gentec-EO

Leader in Laser Beam Measurement Since 1972

Headquarters

445 St-Jean-Baptiste, Suite 160
Québec, QC, G2E 5N7, CANADA

T (418) 651-8003
F (418) 651-1174
1.888.5Gentec (543.6832)

info@gentec-eo.com

Calibration Centers

Quebec City, Canada
Olching (Munich), Germany

Distributed in the UK by

Lambda
photometrics λ

Batford Mill, Harpenden, Herts., UK, AL5 5BZ

T +44 (0) 1582 764334
F +44 (0) 1582 712084

info@lambdaphoto.co.uk
www.lambdaphoto.co.uk

www.gentec-eo.com