

# UNO

Single Channel, Power Monitor



## KEY FEATURES

- 1 Reads ALL Power Detectors**  
Thermopiles and optical detectors of the PH Series
- 2 Large LCD Display**
  - 76 x 57 mm
  - 32 mm digits
- 3 Unique Ergonomic Design**  
Great for both handheld and tabletop use
- 4 Accurate**  
24 bit A/D converter for high resolution measurements
- 5 Single-Button Navigation**  
Direct access and long press access to all the functions
- 6 eXtremely Low Consumption**  
Lasts 670 hours with 4 AA alkaline batteries
- 7 Economical**  
Get the best value for your money with this inexpensive and simple to use power monitor

## NOW AVAILABLE

**W/dBm**

You can now toggle your display between Watts or dBm units

## ACCESSORIES



Additional 9V Power Supply



Wall Support



Protective Pouch



Pelican Carrying Case

## SEE ALSO

POWER DETECTORS	62
OPTICAL DETECTORS	104
OEM DETECTORS	140

# UNO

## SPECIFICATIONS



\*Also traceable to NRC-CNRC

<b>MODEL</b>	UNO
<b>DETECTOR TYPES</b>	Thermopiles, Photo Detectors (PH Series)
<b>DISPLAY</b>	LCD

### POWER METER SPECIFICATIONS

Power Range	5 pW to 10 kW
Thermopile	Autoscale
Photo Detector	Autoscale
Monitor Accuracy	±1 %
Statistics	None

### DETECTOR COMPATIBILITY

Thermopiles	Average Power (W, dBm)
Photo Detectors	Average Power (W, dBm)

### GENERAL SPECIFICATIONS

Digital Display Size	76 x 57 mm LCD
Digit Height	32 mm
Digit Type	High Contrast Fields
Data Display	Real Time
Dimensions (Without Stand)	210W x 122H x 44D mm
Weight (With Batteries)	0.47 kg
Battery Type	4 x AA Alkaline
Battery Life (Estimated)	670 hours with detector
External Power Supply (Optional)	100/240 VAC 50-60 Hz to 9 VDC 1.66 A

### ORDERING INFORMATION

Full Product Name	UNO
Product Number	200982

Specifications are subject to change without notice

MONITORS

ENERGY DETECTORS

POWER DETECTORS

OPTICAL DETECTORS

THZ DETECTORS

OEM DETECTORS

CALORIMETERS

DIFFRACTIVE OPTICS

BEAM DIAGNOSTICS