



Distribution in the UK & Ireland



Lambda Photometrics Limited
Lambda House Batford Mill
Harpenden Herts AL5 5BZ
United Kingdom
E: info@lambdaphoto.co.uk
W: www.lambdaphoto.co.uk
T: +44 (0)1582 764334
F: +44 (0)1582 712084

GiGE VISION GEN*i*CAM



sensor information

sensor	SONY ICX618
type	1/4" progressive scan CCD, Exview HAD technology
resolution	656 × 490 px
exposure time	0,004 ... 60000 ms
pixel size	5.6 × 5.6 µm

acquisition formats

image formats, frame rate max.	Full Frame, 656 x 490 px, max. 160.0 fps
pixel formats	Mono 8 Mono12 Mono12 Packed

image pre-processing

analog controls	Gain (0 ... 26 dB) Offset (0 ... 1023 LSB 14 Bit)
color models	Mono

interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mbits/sec, Fast Ethernet, Transfer Rate 100 Mbits/sec, Connector: SACC-CI-M12FS-8CON-L180-10G
process interface / power supply	SACC-CI-M12MS-8CON-SH TOR 32 / 8 pins

mechanical data

material	aluminum, IP 65 / 67
lens mount	C-mount
width	46 mm
height	46 mm
depth	49,8 mm
weight	≤ 185 g ≤ 220 g (incl. tube)

electrical data

voltage supply	12 ... 24 V DC (external power supply)
range +Vs	36 ... 57 V DC (Power over Ethernet)

electrical data

power consumption	approx. 3.4 W @ 12 VDC and 160.0 fps approx. 3.7 W @ 48 VDC (PoE) and 160.0 fps
-------------------	--

environmental conditions

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 65 / IP 67

digital I/Os

lines	1 input line 3 output lines
-------	--------------------------------

dimension drawing

