



# MODEL 1051

## TEM Mill

A state-of-the-art ion milling and polishing system offering reliable, high performance specimen preparation. It consistently produces high-quality transmission electron microscopy (TEM) specimens with large electron transparent areas from a wide variety of materials.

### Model 1051 TEM Mill specifications

#### Ion sources

Two TrueFocus ion sources  
Variable energy (100 eV to 10 kV) operation  
Beam current density up to 10 mA/cm<sup>2</sup>  
Milling angle range of -15 to +10°  
Choice of single or dual ion source operation  
Independent ion source energy control  
Manual or motorized (optional) ion source angle adjustment  
Adjustable spot size  
Faraday cups for the direct measurement of beam current from each ion source; allows optimization and adjustment of the ion source parameters for specific applications

#### Specimen holder

Designed for improved specimen handling and thermal properties; includes loading station  
Holder clamping mechanism allows for simple specimen loading and double-sided milling to 0° without shadowing  
Specimen holder and loading station with x-y adjustment capabilities (optional)

#### Specimen stage

Specimen size: 3 mm diameter x 250 μm thick  
360° specimen rotation with variable rotation speed and beam sequencing  
Specimen rocking  
Magnetic encoder provides absolute positioning accuracy

## MODEL 1051 TEM Mill

### Model 1051 TEM Mill specifications

<b>Specimen cooling (optional)</b>	<p>Liquid nitrogen conductive cooling with integral dewar and automatic temperature interlocks</p> <p>Achieves temperatures better than -170 °C</p> <p>Dewar access positioned close to instrument operator</p> <p>Ability to program and maintain a specific temperature between ambient and cryogenic</p> <p>Choice of:</p> <ul style="list-style-type: none"><li>• Standard dewar capacity (3 to 5 hours of cryo conditions)</li><li>• Extended dewar capacity (18+ hours of cryo conditions)</li></ul>
<b>Automatic termination</b>	<p>Automatic termination by time, temperature, or laser photodetector (optional)</p>
<b>Vacuum system</b>	<p>Turbomolecular drag pump and an oil-free, multi-stage diaphragm pump</p> <p>Vacuum sensing with a cold cathode, full-range gauge</p>
<b>Vacuum or inert gas transfer capsule (optional)</b>	<p>Allows transfer or storage of specimen at vacuum or in an inert gas environment</p>
<b>Process gas</b>	<p>UHP argon (99.999%); nominal 15 psi delivery pressure required</p> <p>Automatic gas control using two mass flow controllers</p>
<b>User interface</b>	<p>Instrument operation controlled via 10-inch, adjustable touch screen</p> <p>Stack light indicator for determining milling operations status from a distance (optional)</p>
<b>Microscope (optional)</b>	<p>Load lock window accommodates either a:</p> <ul style="list-style-type: none"><li>• 7 to 45 X stereo microscope attachment for direct specimen observation</li><li>• 1,960 X high-magnification microscope and CMOS (complementary metal oxide semiconductor) camera system for site-specific image acquisition and display</li></ul>

## MODEL 1051 TEM Mill

### Model 1051 TEM Mill specifications

#### In situ viewing/imaging

Specimen can be monitored in situ in the milling position when using either the stereo or the high-magnification microscope

Viewing window protected by a programmable shutter that prevents buildup of sputtered material and preserves the ability to observe the specimen in situ

#### Specimen illumination

A light positioned beneath the specimen provides user adjustable, transmitted specimen illumination

Both the high-magnification and stereo microscopes have light sources that provide top-down, user adjustable, reflected sample illumination

#### Enclosure

Width (includes room on either side for service access): 50 in. (127 cm)

Height:

- Minimum height (without microscope or stack light options): 32 in. (81 cm)
- Maximum height (with stack light option): 38 in. (97 cm)

Depth (includes room for service access and exhaust fan air flow): 40 in. (102 cm)

Enclosure design offers easy access to internal components when performing maintenance tasks

#### Weight

161 lb. (73 kg)

#### Power

100/120/220/240 VAC, 50/60 Hz, 720 W

#### Warranty

One year

Distribution in the UK & Ireland



#### Lambda Photometrics Limited

Lambda House Batford Mill  
Harpenden Herts AL5 5BZ  
United Kingdom

**E:** [info@lambdaphoto.co.uk](mailto:info@lambdaphoto.co.uk)

**W:** [www.lambdaphoto.co.uk](http://www.lambdaphoto.co.uk)

**T:** +44 (0)1582 764334

**F:** +44 (0)1582 712084

