

SID4-SWIR-HR

WAVE FRONT SENSOR



↓ SPECIFICATIONS

Wavelength range	0.9 – 1.7 μ m
Aperture dimensions	9.60 x 7.68 mm ²
Spatial resolution	60 μ m
Phase and intensity Sampling	160 X 120
Accuracy	15 nm RMS
Resolution (Phase)	<2nm RMS
Acquisition rate	120 fps
Real-time processing frequency	> 7 fps (full resolution)
Interface	Giga Ethernet
Dimensions	100 x 55 x 63 mm
Weight	455 g

→ The SID4-SWIR-HR wavefront sensor integrates Phasics patented technology with an InGaAs detector. Thanks to its high spatial resolution and great sensitivity, it offers accurate wavefront measurement over its whole spectral range **from 900 nm to 1.7 μ m**.

The SID4-SWIR-HR is an innovative solution for **testing SWIR lens** used in optical communications, inspection instruments or night vision in military and surveillance devices. It provides both MTF and aberrations at once.

The SID4-SWIR-HR also enables characterizing SWIR sources like 1.55 μ m lasers or LEDs for laser guiding systems.

↘ KEY FEATURES

- Extended spectral range from 0.9 to 1.7 μ m
- High resolution – 160 X 120
- High sensitivity - <2nm phase noise through the whole spectral range (compatible with low energy IR source)
- High stability
- Cooled detector
- Compact & Cost effective

PHASICS - The phase control company

Distribution in the UK & Ireland





Distribution in the UK & Ireland



Lambda Photometrics Limited

Lambda House Batford Mill

Harpenden Herts AL5 5BZ

United Kingdom

E: info@lambdaphoto.co.uk

W: www.lambdaphoto.co.uk

T: +44 (0)1582 764334

F: +44 (0)1582 712084