


SID4 UV

WAVE FRONT SENSOR



↓ SPECIFICATIONS

Aperture dimension	7.4 x 7.4 mm ²
Spatial resolution	29.6 μm
Sampling	250 x 250
Wavelength range	250 - 400 nm
Accuracy (absolute)	10 nm RMS
Resolution (Phase)	2 nm RMS
Dynamic	> 200 μm PtV
Analysis rate	2 fps
Acquisition rate	30 fps
Computer connection	Ethernet
Dimensions (WxHxL)	45 x 30 x 100 mm
Weight	250 g

→ The **SID4-UV** wavefront sensor benefits from PHASICS patented technology*. It not only offers an unequalled high resolution (250x250 measurement points) but it is also compact and very easy-to-use. Thus it delivers **fast and accurate** measurement.

It is a cost-effective solution for **testing quality of UV optics** such as lens used in semiconductor systems (MTF, aberrations...). It also allows full **surface inspection** of lens, mirror, wafer...

The SID4-UV is an efficient instrument for ultraviolet **laser beam measurement** (Zernike coefficients, PSF, M², Strehl Ratio, beam profile...)

➤ KEY FEATURES


- Very high resolution: 250x250 phase pixels
- Large analysis pupil: 7.4 x 7.4 mm²
- Broadband
- Compact
- Cost-effective

Distribution in the UK & Ireland



www.lambdaphoto.co.uk

PHASICS - The phase control company



Distribution in the UK & Ireland



Lambda
Genetics Limited
The Mill
Barnet
EN5 8BZ

lambda.co.uk
lambda.co.uk
020 84134
020 84184