Switching Systems

SR10, SR11 & SR12 — Audio switchers for SR1 Audio Analyzer



- · Balanced and unbalanced systems
- XLR and BNC connectors
- 2 × 12 switches
- · Multiple units can be cascaded

SR10, SR11 & SR12 Switchers

The SR10, SR11 & SR12 Switchers bring multiple-channel I/O capability to the SR1 Audio Analyzer. These switching systems allow you to expand the two-input/two-output channels of SR1 by up to 192 channels. They can also be used in general purpose systems to control almost any number of signals.

The SR10 Input Switcher can connect any two of its twelve balanced XLR inputs to SR1. SR11 can connect SR1's two outputs to any of its twelve balanced XLR outputs. SR12 can be configured as either an input or output switcher for unbalanced signals with BNC connectors. All of the switchers can be cascaded using rear-panel connectors to create larger switch matrices.

SR10, SR11 & SR12 Switchers can be controlled from a computer or from SR1 directly. Interfaces include GPIB, RS-232 and Ethernet.

High isolation relays preserve signal integrity and maintain exceptional crosstalk of <-155 dB at 20 kHz. Front-panel LEDs clearly indicate the switch matrix configuration and control status.

Distribution in the UK & Ireland



Characterisation, Measurement & Analysis **Lambda Photometrics Limited** Lambda House Batford Mill Harpenden Herts AL5 5BZ

United Kingdom
E: info@lambdaphoto.co.uk
W: www.lambdaphoto.co.uk

T: +44 (0)1582 764334 F: +44 (0)1582 712084



SR10, SR11 & SR12 Specifications

 $\begin{array}{ll} \text{Max. voltage} & 250\,\text{V}_{\text{rms}}\text{, }220\,\text{V}_{\text{p}} \\ \text{Max. power} & 5\,\text{W or }200\,\text{mA} \end{array}$

Crosstalk (into 600Ω)

SR10 & 11 (Bal) -155 dB @ 20 kHz

−137 dB @ 100 kHz

SR12 (Unbal) -138 dB @ 20 kHz

Series resistance $<300 \,\mathrm{m}\Omega$ (typ.)

Computer interfaces GPIB, RS-232, Ethernet.

Ethernet control is over a simple socket interface or web page.
RS-232 interface can be cascaded with up to 16 switch boxes.
Integrated with SR1 to control up to

16 switch boxes.

Power <10 W, 90 VAC to 264 VAC,

47 Hz to 63 Hz

Dimensions 17" × 1.75" × 11.5" (WHD)

Weight 5 lbs.

Warranty One year parts and labor on defects

in materials and workmanship



SR11 front panel

Ordering Information

SR10 Balanced input switcher
SR11 Balanced output switcher
SR12 Unbalanced I/O switcher
OSR10RM Rack mount kit



SR10 rear panel



SR11 rear panel

Distribution in the UK & Ireland



Characterisation, Measurement & Analysis Lambda Photometrics Limited Lambda House Batford Mill Harpenden Herts AL5 5BZ United Kingdom

E: info@lambdaphoto.co.uk W: www.lambdaphoto.co.uk T: +44 (0)1582 764334

F: +44 (0)1582 712084

