

SPOT LIGHT 5.5" Series



ELECTRICAL:

Input Voltage: See LDM1050 spec
Input Current: See LDM1050 spec
Connector: Quick Connect, 5 pin Reverse Key Euro / Micro

WARNING !!!

**Use Only Spectrum Illumination LDM Driver with Monster Lights.
Do Not Connect Monster Lights Directly to 24VDC!**

MECHANICAL:

Driver: DIN Rail Mount
Dimensions: <http://www.spectrumillumination.com>

ILLUMINATION:

Light Source: LED – 6 Colors, UV & IR
Quantity HB LED's: 18
Light Emitting Pattern: 5.5" / 140mm
LED Life: up to 100,000 hours*.
*Contact us for LED life information

PART NUMBER DESIGNATION: SP5.5-XXX

XXX = Light Color - 470, 505, 530, 590, 630, WHI,
365, 395, 850 & 940

Color	Dash #	λ Dominant Typical	λ Dominant Range	Spectral Half-width $\Delta\lambda_{1/2}$	λ Peak Typical	Units
Infrared	-940	935	n/a	45	940	nm
Infrared	-850	845	n/a	40	850	nm
Red	-630	625	620 - 650	20	638	nm
Amber	-590	590	584 - 598	14	592	nm
Green	-530	530	519 - 561	35	522	nm
Cyan	-505	505	489 - 521	30	503	nm
Blue	-470	470	459 - 491	25	464	nm
Ultra Violet	-395	395	390 - 410	n/a	n/a	nm
Ultra Violet	-365	365	n/a	8	365	nm
White	-WHI	Color Temp 5700 - 7000K				




**Light includes LDM DIN rail mount
constant current driver and 4-meter cable**

Monster Lights have changeable lenses for matching the area of illumination with the working distance



Monster Lenses - P/N SP5.5-XXX/XX

- 12° Narrow (Standard)
- /30 – 30° Medium Angle
- /50 – 50° Medium Angle
- /F – ~70° Wide Angle
- /L – 25° x 6° Angle



*** UV lights are available with 60 degree reflectors only ***

Distribution in the UK & Ireland

Rev. Date: 2009-05-26



**Characterisation,
Measurement &
Analysis**

Lambda Photometrics Limited
Lambda House Batford Mill
Harpenden Herts AL5 5BZ
United Kingdom
E: info@lambdaphoto.co.uk
W: www.lambdaphoto.co.uk
T: +44 (0)1582 764334
F: +44 (0)1582 712084