

700 SERIES OPTICAL ISOLATOR TUNING RANGES			
MODEL NUMBER	TUNING RANGE	ISOLATION	TRANSMISSION
711A	500 TO 645	37 → 40dB	92%
711C	390 TO 500	28 → 30dB	85%
712A	532 TO 715	37 → 40dB	92%
712B	644 TO 780	37 → 40dB	92%
712TGG	700 TO 900	37 → 40dB	92%
713A	650 TO 900	37 → 40dB	92%
713B	790 TO 980	37 → 40dB	92%
714A	780 TO 1000	37 → 40dB	92%
715	965 TO 1135	37 → 40dB	92%
716 (DOUBLE)	SPECIFY CENTER λ	56 → 60dB	88%
716TGG	1064	56 → 60dB	88%

All isolators are supplied with (2) Glan type polarizer's with double escape points and mounting base.

All have 5.0 mm Aperture

Distribution in the UK & Ireland



Lambda Photometrics Limited
 Lambda House Batford Mill
 Harpenden Herts AL5 5BZ
 United Kingdom

**Characterisation,
 Measurement &
 Analysis**

E: info@lambdaphoto.co.uk
W: www.lambdaphoto.co.uk
T: +44 (0)1582 764334
F: +44 (0)1582 712084